

# SAFETY DATA SHEET

Anchor Seal, Inc.

EPOXY HARDENER

## 1. Identification

**1.1 Product Name: SY5822P (Part B)**

**1.2 Material Uses:** Component of an Epoxy System. Adhesive, sealant, encapsulation.

**Issue Date: 9/25/13**

**Supersedes 2/14/13**

**Reason for revision: New format**

**1.3 Manufacturer:**

ANCHOR-SEAL, INC.  
54 Great Republic Drive  
Gloucester, MA 01930  
Tel. 978-515-6004  
Email: [sales@anchorseal.com](mailto:sales@anchorseal.com)

**1.4 In Case of Emergency: INFOTRAC: 1-800-535-5053**

Outside the US and Canada, call 1-352-323-3500

## 2. Hazards Identification

**2.1 OSHA/HCS status: OSHA Hazard Communication Standard (29 CFR 1910.1200).**

**Hazard Category:** Skin and/or eye irritant.

**Classification: CAUTION: Causes skin irritation. May cause sensitization by skin contact. Risk of serious damage to the eyes. May be harmful if swallowed. May cause long-term adverse effects in the aquatic environment.**

**Skin contact:** Causes skin irritation. May cause skin sensitization or an allergic reaction which becomes evident on re-exposure to this material. May be absorbed through the skin.

**Eye contact:** Causes serious eye irritation. May cause burns resulting in permanent damage.

**Ingestion:** Virtually non-toxic after a single ingestion.

**Inhalation:** May cause respiratory irritation. Repeated inhalation may cause lung damage. May cause lung sensitization, an allergic reaction, which becomes evident on re-exposure to this material.

# SAFETY DATA SHEET

Anchor Seal, Inc.

EPOXY HARDENER

2.1 cont.

## Classification according to EC No. 1272/2008 (CLP/GHS)

### Health Hazard statements:

**Skin Irritation** H315 Causes skin irritation.

H317 May cause an allergic skin reaction and sensitization.

**Eye Irritation** H319 Causes serious eye irritation.

**Inhalation** H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

**Oral Toxicity** H303 May be harmful if swallowed.

**Aquatic** H413 This product has not been tested. May cause long lasting harmful effects to aquatic life.

**Xi Irritant** **R36/38, R43**

**N** **R53**

## 2.2 Label Elements

### Hazard pictograms:



**Signal word:** **Warning**

## 2.3 Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear eye protection / face protection, protective gloves & clothing.

P284 In case of inadequate ventilation, wear respiratory protection.

P302 + P352 **IF ON SKIN:** Wash immediately with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice / attention.

**See toxicological information (Section 11)**

**GENERAL INFORMATION:** Read the entire SDS for a more thorough evaluation of the hazards.

# SAFETY DATA SHEET

Anchor Seal, Inc.

EPOXY HARDENER

## 3. Composition/information on Ingredients

| <u>Name</u>  | <u>CAS number</u> |
|--|-------------------|
| <b>3.1 Substances:</b> Mercaptan terminated epoxy curing agent                     | Trade secret      |
| <b>Mixtures:</b> Concentration of composition has been withheld as a Trade Secret. |                   |

## 4. First Aid Measures

**4.1 Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of running tepid water for 15 minutes, occasionally lifting the upper and lower eyelids. If effects occur get medical attention as appropriate.

**Skin contact:** Wash immediately with warm soapy water. Get medical attention if irritation develops. Discard clothing or personal items that cannot be decontaminated.

**Inhalation:** Move exposed person to fresh air and keep comfortable for breathing.  
If not breathing or if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen clothing such as collar, tie, belt or waistband.

**Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately. **Notes to physician:** No specific treatment. Treat symptomatically. Call Poison Control Center if large quantities have been ingested.

### 4.2 Symptoms of exposure:

**Eye contact:** Irritation and redness, pain.

**Skin contact:** Irritation, redness, itching.

**Inhalation:** Dizziness, difficulty breathing if fumes are highly concentrated.

**Ingestion:** Non-toxic after a single ingestion.

**Notes to physician:** To the best of our knowledge, experiences about acute systemic health effects in human beings are not available. No specific antidote known. Symptomatic treatment.

## 5. Fire-Fighting Measures

**NFPA Flammable classification:** Combustible liquid IIIIB

**Flash point:** >180C

### 5.1 Extinguishing Media

**Suitable:** Water fog, carbon dioxide, foam, dry chemical.

**Not Suitable:** None

**5.2 Special hazards:** Combustion products may include: carbon oxides, nitrous gases and ammonia.

**5.3 Special protective actions for fire fighters:** Use protective fire fighting clothing and positive pressure self-contained breathing apparatus (SCBA) to protect against potential harmful and/or irritating fumes. Do not use high volume water jet as this may spread the area of the fire. Use water spray to cool unopened containers.

## 6. Accidental Release Measures

**6.1 Personal precautions:** Isolate area; keep unnecessary and unprotected personnel away from spill area. Avoid contact with skin, eyes and clothing. Use appropriate safety equipment. No health effects expected from the cleanup of this material if contact can be avoided.

**6.2 Environmental precautions:** Avoid disposal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**6.3 Methods for cleaning up:** Contain and absorb large spills with an inert, non-flammable absorbent carrier (such as earth, sand or clay). Shovel into labeled open-top drums or plastic bags for further decontamination if necessary. Wash the spillage area clean with liquid decontaminant. (See section 13 for disposal considerations). Notify applicable government authorities if release is reportable.

# SAFETY DATA SHEET

Anchor Seal, Inc.

EPOXY HARDENER

## 7. Handling and Storage

**7.1 Precautions for safe handling:** Avoid personal contact with the product. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded. Regularly monitor the efficiency of the ventilation system. Avoid the formation and breathing of aerosols, mists and vapors. (See section 8 Exposure control for details). Keep stocks of de-contaminant readily available.

**7.2 Storage:** Keep containers tightly closed and store in a cool, dry well ventilated area.

Suitable materials: mild steel, stainless steel. Unsuitable: aluminum and copper.

## 8. Exposure controls/personal protection

**8.1 Exposure parameters:** None established.

**8.2 Engineering controls:** Ventilation through local exhaust if appropriate.

**Eye/face protection:** Safety glasses, goggles, face mask as appropriate.

**Skin & hand protection:** Protective clothing as necessary to guard against product contact. PVC, neoprene or nitrile rubber gloves.

**Respiratory protection:** Not needed under normal use conditions under adequate ventilation.

**Other protective equipment:** Eye wash stations and emergency showers should be available. The type and degree of personal protective equipment will depend on the specific work operation.

**8.3 Environmental exposure controls:** None established.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties.

|                                  |                              |
|----------------------------------|------------------------------|
| <b>Appearance</b>                | : Viscous liquid             |
| <b>Color</b>                     | : Amber clear or translucent |
| <b>Type of odor</b>              | : Sulfur, Ammonia            |
| <b>Vapor pressure</b>            | : N/D                        |
| <b>Vapor density</b>             | : >1 (air=1)                 |
| <b>Boiling point</b>             | : >200°C                     |
| <b>Flash point</b>               | : >180C                      |
| <b>pH</b>                        | : No data                    |
| <b>Auto ignition temperature</b> | : No data                    |
| <b>Specific gravity</b>          | : 1.10-1.15 grams / cc       |
| <b>Water solubility</b>          | : Slightly soluble           |

## 10. Stability and Reactivity

**10.1 Reactivity:** Reacts with strong acids and strong oxidizing agents.\_

**10.2 Stability:** Stable at room temperature.

**10.3 Hazardous polymerization:** Will not occur by itself. Masses of more than one pound of product plus an epoxy resin will cause irreversible polymerization with considerable heat build up.

**10.4 Conditions to avoid:** Keep away from heat and sources of ignition. Do not smoke.

**10.5 Incompatible materials:** Copper, copper alloys, organic absorbents (sawdust) ketones.

**10.6 Hazardous decomposition products:** Uncontrolled exothermic reaction with epoxy resin releases carbon monoxide, carbon dioxide, nitrogen compounds and ammonia.

# SAFETY DATA SHEET

Anchor Seal, Inc.

EPOXY HARDENER

## **11. Toxicological Information**

**11.1 Acute oral toxicity:** LD50 (rat): >2,000 mg/kg.

**Acute dermal toxicity:** No data

**Acute inhalation toxicity:** No data. No aspiration hazard expected.

**Skin irritation:** Rabbit, slightly irritating.

**Eye irritation:** Rabbit, irritating.

**Product sensitization:** May cause sensitization by skin contact.

## **12. Ecological Information**

**12.1 Toxicity to fish:** LC50: No data

**12.2 Toxicity to microorganisms:** EC50: No data

**12.2 Persistence and biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

## **13. Disposal Considerations**

**13.1 Waste treatment methods:** Do not dump into any sewers, on the ground, or into any body of water. Significant quantities of waste product residues should be processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local requirements. Incineration is the preferred method of disposal.

**Container disposal:** Drain container of all residual material prior to disposal.

## **14. Transport Information:**

**14.1 DOT Road/Rail:** Not regulated

**14.2 Proper shipping name:** Resin compound

**14.3 Ocean transport IMO/IMDG:** Not regulated.

**14.4 Proper shipping name:** Resin compound

**14.4 Air Transport IATA/ICAO:**

**14.5 Proper shipping name:** Aviation regulated liquid, n.o.s. (Polymercaptan)

**14.6 Hazard class:** 9      UN3334      PG: None

Not dangerous goods according to ADR/RID/ADNR. Carriage in accordance with 1.1.4.2.1.

# SAFETY DATA SHEET

Anchor Seal, Inc.

EPOXY HARDENER

## **15. Regulatory Information**

### **15.1 Safety health and environmental regulations/legislation:**

OSHA hazard category: Skin and/or eye irritant.

SARA Title III Section 311/312 (40CFR370): Acute.

SARA Title III Section 313 (40CFR372): No reportable components.

CERCLA Status (40CFR302): No reportable quantity components.

TSCA Inventory status: None listed.

OSHA/NTP/IARC Carcinogen Status: Not listed.

**Chemicals known to the state of California to cause Cancer or reproductive toxicity:** None

**Pennsylvania (Worker and Community Right-to-Know Act): Hazardous Substances List and/or**

**Environmental Hazardous Substance List and/or Special Hazardous Substance List:** To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**State RTK:** MA, NJ, PA None

## **16. Other Information**

**HMIS/NFPA rating:** Health: 1 Fire: 1 Reactivity: 0

(Personal protective equipment selection is best assigned by the user after performing a hazard assessment on the product as it is to be used in the specific work process).